

QUALITY DATE: 20/05/2014
ORDER CODE REPLACES: 21/12/2010

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
WOOLMARK
ANTISOIL
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (± 15%) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE

EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

FIRE RESISTANCE UK

LANO CLASSIFICATION
CLASSIFICATION BS7131

EN 13501-1

BS 4790

ECLIPSE SB/FS
ECI

± 400
COLLECTION
1/10" SAXONY

PIECE DYED

PA



NON WOVEN


WOVEN SYNTHETIC SECONDARY BACKING

± 1.300
± 2.460

± 6,5
± 9,0
± 177.300
± 39,40
± 45,00

±
±

± 25
PILE IN



ANTISTATIC



ADFB6B6B

23723
Z-156.601-1090 - PA 6.6 / 121 / FS

07/238
U3P3E1C0



CL. 23 - CL. 32
Domestic Heavy - Commercial General



LC4

Bfl-s1

QUALITY

DIMENSIONAL STABILITY

EN 986

≤

IMPACT SOUND INSULATION

(±) dB

ISO 140/8

± 27



SOUND ABSORPTION

(±)

α_s

ISO 354 - 125 Hz

± 0,03

(±)

250Hz

± 0,05

(±)

500Hz

± 0,12



(±)

1000Hz

± 0,29

(±)

2000Hz

± 0,5

(±)

4000Hz

± 0,53

SOUND ABSORPTION

(±)

α_w

EN ISO 11654

± 0,2

THERMAL RETENTION

(±) m²/KW

ISO 8302

± 0,074



TOG rating

(±)

± 0,74

PERMANENTLY ANTISTATIC

(±) volt

ISO 6356

< 2000



SURFACE RESISTANCE RoT

(±) ohm

ISO 10965

≤ 10 E11

SURFACE RESISTANCE RdT

(±) ohm

ISO 10965

≤ 10 E10

LIGHTFASTNESS

ISO 105-B02

≥ 5

RUBBINGFASTNESS DRY

ISO 105 X12

≥ 4

RUBBINGFASTNESS WET

ISO 105 X12

≥ 3

WATERFASTNESS CHANGE IN COLOUR

ISO 105-E01

≥ 4

WATERFASTNESS STAINING

ISO 105-E01

≥ 3

LABEL CE



0493-CPR-1038-114375

EN 14041



EN 1307

RECOMMENDED INSTALLATION

ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SB/FS 400</u>	ECI
110	CARMINE
112	CARMINE 2
122	CORAL 2
131	ROSE 1
132	ROSE 2
152	SAHARA 2
202	CHOCOLATE 2
210	TOBACCO
222	DEER
242	BISCUIT
252	MAGNOLIA 2
270	ALMOND
301	MAHOGANY 1
332	APRICOT 2
402	COFFEE 2
430	BAMBOO MAT
672	PETROL 2
762	WEDGWOOD 2
782	STEEL 2
790	MIDNIGHT
800	EBONY
811	CHARCOAL 1
812	CHARCOAL 2
820	SLATE
831	ASH 1
841	MOONSHINE 1

<u>SB/FS 400</u>	ECI
(26)	

