

Article number	10036870 / EIG845FD	Surface structure	beveled 2V, unbrushed	Moisture content	7%±2%
Wood	Oak	Bevel	beveled 2V	Density kg/m³	>500 kg/m³
Grading	Animoso	Number of slotted top layers		Fire protection classification	---
Product type	3-layer parquet	Appearance	Golden floors	Content of formaldehyde	E1
Product group	14 mm Plank 138	Style	Rustic, Classic	PCP content	≤ 5 x 10 ⁻⁶ n
Format	Plank 138	m² per carton	3,04	Brinell Value	---
Dimensions	14 x 138 x 2200 mm	Boards per carton:	10	Breaking strength	NPD
Top layer thickness	3,5 mm	Weight per carton (kg)	23,35	Thermal conductivity	0,14 W/mK
Core material	Spruce / Spruce	m² per pallet	---	Thermal resistance value	11 (m2K/W)
Connection	5G Click	Boxes per pallet	---	Performance classification	---
Floor heating	suitable	Weight per pallet	---	Certificates	---
Treatment	Live Matt lacquer	Nobb.number:	43656132	Antislip performance	---
Colour		EAN Code	7035580047407	Areal thermal resistance	---

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.