

SPECIFICATION

Quality		: LONDON
Product definition		: tufted loop pile
Gauge		: 1/8"
No. of tufts	ISO 1763	: ± 117000/m ² (± 97826 /yd ²)
Pile fibre		: 100% polyamide 6.0
Pile weight		: 520 gr/m ² ± 5% (± 15 oz/yd ²)
Pile height	ISO 1766	: 3.5 mm ± 5%
Primary backing		: PA/PES non-woven - Colback
Tile backing		: Polyflex with a non-woven fabric
Total thickness	ISO 1765	: 7.2 mm ± 7,5%
Total weight		: 4200 gr/m ² ± 7,5% (± 124 oz/yd ²)
Tile size		: 50 x 50 cm (± 19.7" x 19.7")
Tiles per box		: 20

PERFORMANCE

Use classification		: Class 33
Castor chair test	EN 985	: A, continues use
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361/EN 1471	: pass
Thermal isolation	ISO 8302	: 0.09 m ² K/W
Dimensional stability	ISO 2551	: pass

ELECTROSTATIC PROPERTIES

Walk on test	ISO 6356	: -0.1 kV
Horizontal electrical resistance	ISO CD 10965	: 8x10 ⁹ Ω
Vertical electrical resistance	ISO CD 10965	: 4x10 ⁹ Ω
Static loading		: anti-static

FLAME PROPERTIES

Reaction to fire	EN ISO 11925-2	
	EN ISO 9239-1	: B _{fl} - s1
Hot metal nut test	BS 4790	: Low Radius

COLOUR FASTNESS PROPERTIES

Light	ISO 105 B02	: > 5.0
Rubbing, dry	ISO 105 X12	: 4.5
Rubbing, wet	ISO 105 X12	: 5.0
Shampoo	BS 1006	: 4.5
Water	ISO 105 E01	: 5.0
Water stains	TNO W 6024	: 5.0

GENERAL

Recommended maintenance:
Pile direction:


Laying instructions:

Best results are obtained when cleaned with a dry shampoo method.

Directional arrows are printed on the back of each tile.

Best results are obtained when laid checkerboard.

Tiles require no underlay, nailing, gluing or sewing and may be laid loose on a flat, dry, non-slippery floor. When tiles are laid on parquet, vinyl or in open areas larger than 30 m² it is advisable to use double sided adhesive tape on every 8th row or a tackifier.



COLOURS

1236 Blue	1237 Seablue
1280 Blue grey	1283 Marine blue
1279 Black	1278 Charcoal

1265 Red	1205 Azuur
1276 D. grey	1290 Beige
1209 Earth	1208 Brown