

QUALITY
ORDER CODE

DATE: **29/10/2019**
REPLACES: 2/09/2019

WIDTH (±) cm
TYPE
GAUGE AND TYPE
TEXTURING
DYEING/PRINT METHOD

PILE COMPOSITION
FIBRE BRAND
MOTHPROOF

PRIMARY BACKING

SECONDARY BACKING

PILE WEIGHT (±) gr/m²
TOTAL WEIGHT (±) gr/m²

EFFECTIVE PILE HEIGHT (±) mm
TOTAL HEIGHT (±) mm
NUMBER OF KNOTS (±) m²
STITCHES OVER WIDTH (±) / 10 cm
STITCHES OVER LENGTH (±) / 10 cm

REPEAT TUFTING DESIGN L/W (±) mm
REPEAT PRINTING DESIGN L/W (±) mm

ROLL LENGTH (±) m
PILE IN/OUT

LANO CLASSIFICATION

BEDROOM
LIVING ROOM
OFFICE
CASTOR ROLLCHAIRS DOMESTIC USE
CASTOR ROLLCHAIRS PROFESSIONAL USE
STAIRS DOMESTIC USE
STAIRS PROFESSIONAL USE
ELECTROSTATIC BEHAVIOUR
UNDERFLOOR HEATING
BATH ROOM
NON-FRAY
PERSONAL COMPUTER

PRODIS-NUMBER

GUT-NUMBER
DIBT

UPEC n°
CLASSIFICATION

HQE
EN 1307

ADDITIONAL CHARACTERISTICS EN 1307

LUXURY CLASS

FIRE RESISTANCE EUROPE

EN 13501-1

FIRE RESISTANCE UK

BS 4790

LANO CLASSIFICATION
CLASSIFICATION BS7131

SWEET ELEGANCE SB
SWE

± 400-500
COLLECTION
1/8" CUT PILE

SOLUTION DYED

PP

WOVEN

WOVEN SYNTHETIC SECONDARY BACKING

± 2.190
± 3.160

± 16,0
± 18,0
± 143.325
± 31,50
± 45,50

±
±

± 25
PILE IN

✓
✓

✓

NO SHOCK
✓

Cl. 22
Domestic General/Medium



LC5



Efl



LOW RADIUS

HEAVY DOMESTIC / GENERAL NON-DOMESTIC

QUALITY

IMPACT SOUND INSULATION	(±) dB	ISO 140/8
THERMAL RETENTION	(±) m ² /KW	ISO 8302
TOG rating	(±)	
PERMANENTLY ANTISTATIC	(±) volt	ISO 6356
LIGHTFASTNESS		ISO 105-B02
RUBBINGFASTNESS DRY		ISO 105 X12
RUBBINGFASTNESS WET		ISO 105 X12
WATERFASTNESS CHANGE IN COLOUR		ISO 105-E01
WATERFASTNESS STAINING		ISO 105-E01

SWEET ELEGANCE SB

± 25



± 0,24



± 2,4

≤

≥ 5

≥ 3-4

≥ 3

≥ 3-4

≥ 2-3



ALL-OVER STICK DOWN
WITH EC1 APPROVED ADHESIVE

LABEL CE

RECOMMENDED INSTALLATION

MANUFACTURING TOLERANCE

(±) These details are approximate. Due to method of manufacture perfect pattern and/or colour matching cannot be guaranteed. In cut-pile carpeting, in rare cases, shading/pile reversal may occur without affecting its fitness for use. Shading/pile reversal can not be considered as a manufacturing or a material defect and will not affect the durability of the carpet.

AVAILABLE FROM

AVAILABLE FROM

COLOURS

<u>SB 400</u>	SWE	<u>SB 500</u>
0230	FLAX	0230
0240	CREAM	0240
0430	BAMBOO MAT	0430
0440	IVORY	0440
0450	SAND	0450
0820	SLATE	0820
0830	ASH	0830
0840	MOONSHINE	0840
0850	MOONBEAM	0850
0860	GRANITE	0860
0870	SILVER	0870
0880	PEARL	0880

<u>SB 400</u>	SWE	<u>SB 500</u>



WE RESERVE THE RIGHT TO ALTER TECHNICAL SPECIFICATIONS WITHOUT PRIOR NOTICE

(12)

(12)