



Technical Specifications SUPER TEX 2.0

GPMF: 946/5

Floor covering

1. Technical Specifications

Issued by: Graboplast Floor Covering Manufacturers Ltd. (H-9023 Győr, Fehérvári út 16/b.)

Purpose: Technical data of the resilient PVC flooring according to **EN 650** sheet vinyl.

2. Application Area

For use area of general domestic (23-31)

Floorcovering for household application with general traffic.

For information on handling of the product (storing, installation, maintenance) see www.graboplast.com.

3. Technical Data of the Product

Parameter	Dimension	Specification	Tolerance	Test method
Width	cm	200; 250; 300; 350; 400	min.	EN ISO 24341
Thickness	mm	3.0	+0.18; -0.15	EN ISO 24346
Weight	g/m ²	1900	+13%; -10%	EN ISO 23997
Wear layer density	kg/m ³	1250	±50	EN ISO 23996
Dimensional stability (L/C)	%	±0.40	max.	EN ISO 23999
Curling	mm	8	max.	EN ISO 23999
Light fastness	grade	6	min.	EN ISO 105-B02 3. method
Adhesion resistance of top layer (L/C)	N/50 mm	50/50	min.	EN ISO 24345
Abrasion group	-	T	-	EN 660-1
Wear layer thickness	mm	0.20	+13%; -10%	EN ISO 24340
Furniture leg	-	no damage	-	EN 424
Foot comfort, indentation after loading of 15 s	mm	0.40	min.	EN ISO 24343
Residual indentation	mm	0.40	max.	EN ISO 24343

4. Informative Data of the Product

Parameter	Dimension	Specification	Tolerance	Test method
Chemical resistance	-	high resistance	-	EN ISO 26987
Abrasion resistance (H18 wheel)	mg/1000 rev.	250	max.	ISO 9352
Reaction to fire	class	C _f S ₁	-	EN 13501-1
Standard roll length	m	20	-	EN ISO 24341

Valid from: 28.01.2015

Approved by:

Németh T. Balázs

Leader of Quality Management



floor.wood

GRABOPLAST | FLOOR COVERING MANUFACTURERS LTD.

Fehérvári St. 16/b, Győr, 9023

Phone: +36 96 506 100, Fax: +36 96 506 196 | E-mail: mail@graboplast.hu

Reg. number: 08-10-001859 | Tax number: 14986042-2-08

VAT number: HU14986042