






















# TECHNICAL CHARACTERISTICS

<b>ambra Multi-Layer</b> Long-lasting multi-layer floor (Multi-Layer) according to ISO 20326:2016 (formerly EN 14085) for glueless installation				
	<b>ambra wood</b> Multi-Layer	<b>ambra stone</b> Multi-Layer		
<b>Format</b>	1200 x 212 mm	591 x 287 mm		
<b>Product thickness</b>	9 mm	9 mm		
<b>Planks, tiles / m<sup>2</sup> per box</b>	8 / 2.04 m <sup>2</sup>	9 / 1.53 m <sup>2</sup>		
<b>Boxes / m<sup>2</sup> per pallet</b>	48 / 97.92 m <sup>2</sup>	60 / 91.80 m <sup>2</sup>		
<b>Guarantee</b>	15 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de			
<b>Classification</b>			<b>Product composition</b>	
	<b>Utilization class 23</b> Heavy-duty use in the domestic area EN ISO 10874	Corridors, living rooms, kitchens, home offices	1	<b>Surface sealing</b>
	<b>Utilization class 31</b> Medium use in the commercial sector EN ISO 10874	Hotel rooms, small offices	2	<b>Surface texture</b> various embossings
	Wear layer binder content EN ISO 10582	Type I	3	<b>Wear layer</b> Thickness 0.3 mm
	Wear resistance EN 660-2	Group T acc. to DIN EN 649:2011-05	4	<b>Decor</b> Decor film
	Reaction to fire EN 13501-1	B <sub>fl</sub> - s1	5	<b>Base layer</b>
	Anti slip category DIN 51130	R 9	6	<b>Core board</b> Aqua-Protect®
	Slip resistance EN 13893	μ ≥ 0.30 - DS	7	<b>Profile connection</b> LocTec® technology 
	Anti-static properties EN 1815	≤ 2 kV	8	<b>Profile sealing</b>
	Staining and chemical resistance EN ISO 26987	Good resistance according to the concentration and residence time	9	<b>Insulation mat</b> Sound-Protect Eco
	Light fastness EN ISO 105-B02	≥ 6	<b>Certifications</b>	
	Residual indentation EN ISO 24343-1	~ 0.02 mm	 <p>windmüller flooring products WFP GmbH Nord-West-Ring 21 D-32832 Augustdorf</p> <p>- 10 - Multi-Layer DUP: 1601001 EN 14041:2004</p> <p>Multi-Layer Flooring to be used within a building.</p>  <p>Information representative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)</p> 	
	Castor chair test EN 425 / ISO 4918	Type W – no visible change		
	Thermal resistance EN 12667	~ 0.06 (m <sup>2</sup> K)/W		
	Impact sound reduction EN ISO 16251-1	up to 14 dB		
	Formaldehyde emission EN 717-1	E1		
	Disposal	<u>Private:</u> Possible with normal domestic refuse <u>Commercial:</u> Refuse-key-no. AVV 170203		

### Relevant information:

- Underfloor heating: In conjunction with suitable underlay material, suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by windmüller flooring products WFP GmbH.