

## Ash White Marcato

## Product details / Technical properties

Article number	10035759 / ASGL82TD	Bevel	square edged	Moisture content	5-9%
Wood	Ash	Number of slotted top layers	0	Fire protection classification	Dfl-s1
Grading	Marcato	Surface structure	unbrushed	Content of formaldehyde	E 1
Product type	3-layer parquet	m² per carton	2,84	PCP content	NPD
Format	14mm Longstrip 3-Strip	Boards per carton	6	Brinell Value	36
Dimensions	14 x 215 x 2200 mm	Weight per carton (kg)	21	Shrinking and swelling	
Top layer thickness	3,5 mm	m² per pallet	142	Breaking strength	NPD
Core material	Spruce / Spruce	Boxes per pallet	50	Thermal conductivity (W/(m*K)	0,13
Connection	5G Click	Weight per pallet (kg)	1050	Thermal resistance (m <sup>2*</sup> K)/W	0,11
Floor heating	suitable	EN Norm	EN 13489	Antislip performance (CE)	USRV 33
Treatment	Live Matt lacquer white	FSC claim	controlled sources	Antislip performance (DIN)	R9
Appearance	Light floors	Performance classification	Class 1	Nobb.number	50693542
Colour	White	Density	>= 500kg/m <sup>3</sup>	EAN Code	7035580183082















The mark of responsible forestry

Wood is a product of nature – each tree has its own structure and individual colour combination. An image or a sample will therefore never be able to give you a complete picture of the finished floor. Please also note that the colour may change when exposed to light. As a guideline, darker wood species will get a more golden tone, whereas lighter species will become slightly darker. Cracked knots are filled with putty, so small gaps between the putty and wood may appear.

