

























# TECHNICAL CHARACTERISTICS

kingsize – ambra		wineo	
Covering type according to EN ISO 10582: Heterogeneous resilient-flooring to glue			
	<b>kingsize – ambra</b>		
<b>Format</b>	1505 x 235 mm		
<b>Product thickness</b>	2.5 mm		
<b>Planks, tiles / m<sup>2</sup> per box</b>	10 / 3.54 m <sup>2</sup>		
<b>Boxes / m<sup>2</sup> per pallet</b>	68 / 240.72 m <sup>2</sup>		
<b>Guarantee</b>	15 years – Guarantee for private use according to Windmüller warranty conditions – www.wineo.de		
<b>Classification</b>		<b>Product composition</b>	
	<b>Utilization class 23</b> Heavy-duty use in the domestic area EN ISO 10874	Corridors, living rooms, kitchens, home offices	1 <b>Surface sealing</b>
	<b>Utilization class 31</b> Medium use in the commercial sector EN ISO 10874	Hotel rooms, small offices	
	<b>Wear resistance</b> EN 660-2	Group T	2 <b>Wear layer</b> Thickness 0.3 mm
	<b>Reaction to fire</b> EN 13501-1	B <sub>fl</sub> - s1	3 <b>Decor film</b> Surface texture - various embossings
	<b>Anti slip category</b> DIN 51130	R 9	4 <b>Base layer</b>
	<b>Slip resistance</b> EN 13893	$\mu \geq 0.30$ - DS	5 <b>Backing</b>
	<b>Anti-static properties</b> EN 1815	$\leq 2$ kV	DESIGN FLOORING to glue 
	<b>Staining and chemical resistance</b> EN ISO 26987	Good resistance according to the concentration and residence time	Bevelled edge
	<b>Light fastness</b> EN ISO 105-B02	$\geq 6$	<b>Certifications</b>
	<b>Residual indentation</b> EN ISO 24343-1	$\sim 0.02$ mm	<div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;">  <p>windmüller flooring products WFP GmbH Nord-West-Ring 21 D-32832 Augustdorf</p> <p>- 07 -</p> <p>Elastischer Bodenbelag DUP: 0401001 EN 14041:2004</p>  <p>Resilient Flooring to be used within a building.</p> </div> <div style="border: 1px solid black; padding: 5px; margin-bottom: 5px;"> <p>ÉMISSIONS DANS L'AIR INTÉRIEUR</p>  <p>Information représentative des émissions dans l'air intérieur des substances volatiles présentant un risque de toxicité par inhalation, sur une échelle de classe allant de C (fortes émissions) à A+ (très faibles émissions)</p> </div> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>Schadstoffgeprüft Emissionsgeprüft</p> </div> <div style="text-align: center;">  <p>70 710 4681-1</p> </div> </div> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  </div> <div style="text-align: center;">  </div> </div>
	<b>Castor chair test</b> EN 425 / ISO 4918	Type W – no visible change	
	<b>Thermal resistance</b> EN 12667	$\sim 0.01$ (m <sup>2</sup> K)/W	
	<b>Impact sound reduction</b> EN ISO 16251-1	$\sim 4$ dB	
	<b>Dimension stability</b> EN ISO 23999	$\sim 0.15$ %	
<b>Disposal</b>	<b>Private:</b> Possible with normal domestic refuse <b>Commercial:</b> Refuse-key-no. AVV 170203		



**Relevant information:**

- Underfloor heating: Suitable for all conventional hot water underfloor heating and electrical systems regulated up to a surface temperature of 27° C.
- Cleaning and care: see separate cleaning & care instruction.
- Technical subjects can be changed by windmüller flooring products WFP GmbH.