

# EMINENCE technical data

CERTIFICATION & CLASSIFICATION	STANDARDS
Type of floor covering	EN ISO 10582
CE certification	EN 14041
Classification	EN ISO 10874

TECHNICAL CHARACTERISTICS	STANDARDS
Total thickness	EN ISO 24346
Wear layer thickness	EN ISO 24340
Total weight/m <sup>2</sup>	EN ISO 23997
Polyurethane reinforcement	
Wear layer binder content	EN ISO 10582
Form of delivery	EN ISO 24341 Sheet (rolls)

TECHNICAL PERFORMANCES	STANDARDS
Dimensional stability	EN ISO 23999
Curl resistant to heat	EN ISO 23999
Impact sound reduction	EN ISO 717/2 NF S31-074
Residual indentation	EN ISO 24343-1
Reaction to fire	EN 13501-1
Slip resistance	DIN 51130 EN 13893
Furniture leg	EN 424
Castor chair	ISO 4918
Total VOC emissions	ISO 16000-6
Light fastness	EN ISO 105-B02
Chemical resistance	EN ISO 26987
Static electrical discharge	EN 1815 EN 1081
Thermal resistance Underfloor heating Colours	EN 12667

EMINENCE
Heterogeneous compact floor coverings based on poly (vinyl chloride)
Yes
Commercial: 34 Industrial: 43

EMINENCE
2.0 mm
0.70 mm
2650 g
Top Clean™
Type I
Approx. 23 r m x 200 cm Art. no. 25104 ___ 3 digit colour number
Approx. 23 r m x 400 cm Art. no. 25103 ___ 3 digit colour number

EMINENCE
≤ 0.10 %
≤ 8 mm
7dB Class C
Required value: ≤ 0.10 mm Best measured value: 0.04 mm
B <sub>fl</sub> ≤ 1 glued over concrete and wood substrates
R10 ≥ 0.30
No damage
No damage
≤ 100 µg/m <sup>3</sup> ≥ 6
High resistance < 2kV on concrete R <sub>f</sub> > 10 <sup>9</sup> Ω
0.02 m <sup>2</sup> K/W Suitable 26

The above information is subject to modification for the benefit of further improvement. (10/16).

Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for these instructions.

CUSTOMS TARIFF : 4820 5000 00

References	NCS No.	Welding Rod No.
000	S 3020-Y10R	1287 432
001	S 4020-Y20R	1287 153
002	S 5020-Y20R	1287 477
003	S 5020-Y30R	1294 429
004	S 3005-Y20R	1287 501
005	S 3005-Y20R	1291 839
006	S 4010-Y30R	1287 560
007	S 6005-Y20R	1287 556
008	S 3005-Y50R	1287 696

References	NCS No.	Welding Rod No.
009	S 4005-Y50R	1287 591
010	S 3005-Y20R	1287 544
011	S 5502-Y	1287 308
012	S 2005-Y30R	1287 402
013	S 4005-Y20R	1287 575
014	S 4010-Y10R	1287 737
015	S 5005-Y20R	1287 537
016	S 2005-Y50R	1287 805
017	S 4502-R	1287 730

References	NCS No.	Welding Rod No.
018	S 5502-Y	1287 525
019	S 7502-Y	1287 576
084	S 3020-Y	1287 426
085	S 3010-B90G	1287 149
086	S 3020-Y60R	1287 286
087	S 3502-Y	1287 532
088	S 4005-Y50R	1291 847
090	S 2502-Y	1287 290



www.professionals.tarkett.com